

Safety Data Sheet According to Regulation (EC) No 1907/2006

U-40 °C Super Insulated Transformer Oil

Version 1.0

Issue date: 8/12/2017 **Revision date: 8/12/2017**

SDS Record Number: SINOPEC CCNT-I-008

Section 1 Identification of the substance/mixture and of the company/undertaking

	• • •						
1.1 Product identifier:							
Identification on the label/Trade name:	U-40°C Super Insulated Transformer Oil						
Additional identification:	Not available						
Identification of the product:	See section 3						
Index Number:	Not available						
REACH registration No.:	01-2119474878-16-0008						
1.2 Relevant identified uses of the substance	and uses advised against:						
1.2.1 Identified uses:							
U -40 $^{\circ}\mathrm{C}$ Super Insulated Transformer Oil s	uitable for insulation and cooling medium in the oil-immersed transformer.						
1.2.2 Uses advised against:							
Not available.							
1.3 Details of the supplier of the safety data s	heet:						
Supplier(Only representative):	-						
Supplier(Manufacturer):	SINOPEC LUBRICANT CO.,LTD						
Address:	No. 6 Anning Zhuang West Road, Haidian District, Beijing, P.R. China						
	Post number:100085						
Contact person(E-mail):	csc.lube@sinopec.com						
Telephone:	0086-400-810-9886						
Fax:	0086-10-82410856						
1.4 Emergency telephone Number:							
0086-400-810-9886							
Available outside office hours?	YES NO X						
Section 2 Hazards Identification							
2.1 Classification of the substance/mixture:							
2.1.1 Classification:							

The mixture is classified as following according to REGULATION (EC) No 1272/2008:

REGULATION (EC) No 1272/2008				
Hazard classes/Hazard categories	Hazard codes			
N/A	N/A			

For full text of H- phrases: see section 2.2.

2.2 label elements:

Hazard Pictograms: No hazard pictogram is used.

Signal Word(S): No signal word is used.

Hazard Statement: Not applicable. Not applicable. **Precautionary statement:**

SINOPEC LUBRICANT CO.,LTD.

Product name: U-40°C Super Insulated Transformer Oil

Version #: 1.0 Issue date: 8-12-2017. Revision date: 8-12-2017.



2.3 Other hazards:

Not available.

Section 3 Composition/information on ingredients

Substance/Mixture: Mixture

Ingredient(s):

Chemical Name	Registration N	o. CAS No.	EC No.	Concentration	Classificatio n
Lubricating oils					
(petroleum),C15-C30,	01-2119474878	3-16-0008 72623-86-	0 276-737-9	100%	Not Classified
hydrotreated neutral o	il-based				

Section 4 First aid measures

4.1 Description of first aid measures:

In all cases of doubt, or when symptoms persist, seek medical attention.

4.1.1 In case of inhalation:

No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

4.1.2 In case of skin contact:

No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

4.1.3 In case of eyes contact:

No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

4.1.4 In case of ingestion:

No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed:

In the case of high temperature long-term inhalation of oil mist or vapors may cause respiratory irritation. Prolonged or repeated skin contact can cause irritation or inflammation of the skin. Eye contact can cause mild irritation to the eyes. Ingestion too much may lead to stomach irritation, vomiting and diarrhea.

4.3 Indication of any immediate medical attention and special treatment needed:

If skin irritation or rash occurs, get medical advice/attention.

Section 5 Fire-Fighting measures

5.1 Extinguishing media:

Suitable extinguishing media: Spray, foam, fire extinguishers, carbon dioxide fire extinguisher, dry powder

fire extinguisher

Unsuitable extinguishing media: Do not water.

5.2 Special hazards arising from the

substance or mixture

This product has a flash point over 150°C and it belongs to non-dangerous products. When it meets fever case, the fire and strong oxidants, it can cause a fire. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be

evolved when this material undergoes combustion.

5.3 Advice for firefighters: Must wear breathing apparatus in confined spaces when close to the ignition

point.

Section 6 Accidental release measures

SINOPEC LUBRICANT CO.,LTD.

Product name: U-40°C Super Insulated Transformer Oil SDS EU Version #: 1.0 Issue date: 8-12-2017. Revision date: 8-12-2017.



6.1 Personal precautions, protective equipment and emergency procedures:

6.1.1 For non-emergency personnel:

Cut off the fire source, immediately contact the operating staff. Keep unrelated people rapidly evacuating to safe areas and isolation. As far as possible to cut off the source of leakage, prevent entering into sewers, drains, water and space. Refer to Chapter 8 of MSDS or the relevant fire-fighting procedures.

6.1.2 For emergency responders:

Wear an appropriate NIOSH/MSHA approved respirator if vapor is generated.

6.2 Environmental Precautions:

Before operating staff arrive at the scene, as much as possible to make the spilled material under control. For a small amount of leakage, use sawdust, sand, soil or other adsorbent to collect leaking liquid and place it in a sealed, liquid-proof container, waiting to be processed; For a large number of leakage, build a causeway or dig to collect it, Ensure that it does not flow into the sewers, rivers, water and lowlands. Place spilled material in appropriate container for disposal. Report to relevant departments when the soil and plant was polluted.

6.3 Methods for Containment and Cleaning up:

For a large number of leakage, Pump it into a container with a vacuum pump; For a small amount of leakage, use sawdust, sand, soil, oil-absorbing cotton or other adsorbent to prevent proliferation and load it into the sealed container for processing; For land leakage, take protective measures and cut off the sources of pollution, reduce to a minimum for the pollution of surface water; For waterway leakage, Immediately use the oil boom to prevent the loss of oil, warn the surrounding vessel and, when necessary, use suitable dispersants. If significant spillages can not be processed, should inform the local authorities.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

Section 7 Handling and storage

7.1 Precautions for safe handling:

7.1.1 Protective measures:

Avoid long or repeated contact with skin, if contact, thoroughly wash it. If you are at risk of inhaling steam, spray or smoke, Please use local exhaust ventilation device. When transport, please lightly touch it to prevent the package and containers destroy.

7.1.2 Advice on general occupational hygiene:

7.2 Conditions for safe storage, including any incompatibilities:

Do not eat, drink and smoke in work areas. Wash hands after use. Remove contaminated clothing and protective equipment before entering eating areas. Keep the container sealing, do not store it into open container or container without labels. Keep it cool, dry and ventilate. Keep it from strong oxidant, fire, heat source and inflammable. Store it in normal temperature. Empty container may leave partly products, do not cut or weld, do not leave it in fire or high temperature.

7.3 Specific end use(s): Not applicable.

Section 8 Exposure Controls/Personal Protection

8.1 Control parameters:

Not available. 8.1.1 Occupational exposure limits: Not available. 8.1.2 Additional exposure limits under the

conditions of use:

Not available.

8.1.3 DNEL/DMEL and PNEC-Values:

8.2 Exposure controls:

8.2.1Appropriate engineering controls: Use adequate ventilation to keep airborne concentrations low.

8.2.2 Individual protection measures, such as personal protective equipment:

SINOPEC LUBRICANT CO.,LTD.

Product name: U-40°C Super Insulated Transformer Oil

Version #: 1.0 Revision date: 8-12-2017. Issue date: 8-12-2017.



Eye/face protection: No special eye protection is normally required. Where splashing is possible,

wear safety glasses with side shields as a good safety practice.

Hand protection: Suggested materials for protective gloves include: Neoprene, Nitrile Rubber.Body protection: No special protective clothing is normally required. Where splashing is

possible, select protective clothing depending on operations conducted

physical requirements and other substances in the workplace.

Respiratory protection: No respiratory protection is normally required. No respiratory protection is

ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of

material. If user operations generate an oil mist, determine if airborne

concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate

protection.

Thermal hazards: Wear suitable protective clothing to prevent heat.

8.2.3 Environmental exposure controls: Avoid discharge into the environment.

According to local regulations, Federal and official regulations.

Section 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Appearance: Oil liquid

Colour: Transparent, colorless to pale yellow

Odorless/Light petroleum.

Odour threshold:Not availablepH:Not availableMelting point/range ($^{\circ}$):Not available

Pour point: -54°C (typical data)

Boiling point/range ($^{\circ}$ C): >250 $^{\circ}$ C

Flash point (℃): 154°C (closed cup) (typical data)

Evaporation rate:

Flammability limit - lower (%):

Flammability (solid, gas):

Ignition temperature (℃):

Upper/lower flammability/explosive limits:

Not available

Not available

Vapour pressure (40°C): <5kPa

Vapour density: Not available

Density: 835.1 kg/m³ (20°C) (typical data)

Bulk density (kg/m³):

Water solubility (g/l):

n-Octanol/Water (log Po/w):

Not available

Auto-ignition temperature: $> 270^{\circ}$ C Decomposition temperature: $> 280^{\circ}$ C

Kinematic viscosity: 10.30 mm/s² at 40 °C (typical data)

SINOPEC LUBRICANT CO.,LTD.

Product name: U-40°C Super Insulated Transformer Oil

Version #: 1.0 Issue date: 8-12-2017. Revision date: 8-12-2017. 4



Not available **Explosive properties:** Not available Oxidising properties: Not available Molecular Formula: **Molecular Weight:** Not available

9.2. Other information:

Fat solubility(solvent- oil to be specified)

etc:

Not available Surface tension: Dissociation constant in water(pKa): Not available **Oxidation-reduction Potential:** Not available

DMSO extractable compounds

for base oil substance(s) < 3%

according to IP346

Section 10 Stability and reactivity

10.1 Reactivity: The substance is stable under normal storage and handling conditions.

Not available

10.2 Chemical stability: Stable at room temperature in closed containers under normal storage and

handling conditions.

10.3 Possibility of hazardous reactions: No dangerous reactions known.

10.4 Conditions to avoid: Incompatible materials. Avoid temperatures exceeding the flash point.

10.5 Incompatible materials: May react with strong acids or strong oxidizing agents, such as chlorates,

nitrates, peroxides, etc.

10.6 Hazardous decomposition products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons.

Section 11 Toxicological information

11.1 Information on toxicological effects:

Acute toxicity:

Not available LD50(Oral, Rat):

LD50(Dermal, Rabbit): >5g/kg

LC50(Inhalation, Rat): Not available Skin corrosion/Irritation: Not classified Not classified Serious eye damage/irritation: Not classified Respiratory or skin sensitization: Germ cell mutagenicity: Not classified Not classified Carcinogenicity: Not classified Reproductive toxicity: Not classified STOT- single exposure: Not classified STOT-repeated exposure: Not classified Aspiration hazard:

Section 12 Ecological information

12.1 Toxicity:

Distillates (petroleum), hydrotreated light paraffinic(CAS#64742-55-8)

Acute toxicity		Time	Species	Method	Evaluation	Remarks
LL50	> 100 mg/L	96h	Fish OECD 203		N/A	N/A
EL50	> 10000 mg/L	48h	Daphnia	OECD 202	N/A	N/A

SINOPEC LUBRICANT CO.,LTD.

Product name: U-40°C Super Insulated Transformer Oil SDS EU Version #: 1.0 Revision date: 8-12-2017. Issue date: 8-12-2017.



EC50 N/A 72h Algae OB	PECD 201 N/A N/A
-----------------------	------------------

12.2 Persistence and degradability: This material is not expected to be readily biodegradable. This material has bioaccumulation potential component. 12.3 Bioaccumulative potential: 12.4 Mobility in soil: The material will be adsorbed to soil and not be mobile.

12.5 Results of PBT&vPvB assessment: Not available. 12.6 Other adverse effects: Not available.

Section 13 Disposal considerations

13.1 Waste treatment methods: The material should be disposed of by incineration in a chemical incinerator in

compliance with national and regional requirements.

Section 14 Transport information							
	Land transport(ADR/RID) Sea transport (IMDG)		Air transport (ICAO/IATA)				
UN-Number	Not regulated	Not regulated	Not regulated				
UN Proper shipping name	Not regulated	Not regulated	Not regulated				
Transport hazard Class	Not regulated	Not regulated	Not regulated				
Packaging group	Not regulated	ot regulated Not regulated					
Environmental hazards	No	No	No				
Special precautions for user	See section 2.2	See section 2.2	See section 2.2				
Transport in bulk according to Annex II of Marpol and the IBC Code	Not regulated	Not regulated	Not regulated				

Section 15 Regulation information

15.1	Safety.	. health an	d environmental ı	equiations/l	eaislation s	specific fo	or the sub	stance or	mixture
		,a.iii aii	a	0941410110/1		, p = = : : = : =		J	

Relevant information regarding authorization: Not applicable. Relevant information regarding restriction: Not applicable.

Employment restrictions concerning young person must be observed. Other EU regulations:

For use only by technically qualified individuals.

Other National regulations: Not applicable

15.2 Chemical Safety Assessment has been carried YES

out?

NO Χ

Section 16 Other information

16.1 Indication of changes:

Version 1.0 Amended by (EU) 2015/830

16.2 Training instructions:

Not applicable.

16.3 Further information:

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

16.4 Notice to reader:

Employers should use this information only as a supplement to other information gathered by them, and should make

SINOPEC LUBRICANT CO.,LTD.

Product name: U-40°C Super Insulated Transformer Oil SDS EU Revision date: 8-12-2017.



independent judgment of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with anyother product or process, is the responsibility of the user.